



ClimaGrün

Product data sheet

Item number: 102020

Filter fleece CG-FV 200

prevents fine particles from being washed into the drainage layer and guarantees high water permeability



Technical data

Material	PP (polypropylene)
Nominal thickness	approx. 1,9 mm
Weight	approx. 200 g/m ²
Opening width O ₉₀ (EN ISO 12956)	approx. 0,1 mm
Static puncture resistance (EN ISO 12236)	approx. 2.350 N
Geotextile robustness class	GRC 3
Water permeability H ₅₀ (EN ISO 11058)	approx. 115 l/m ² s
Dimensions	Dimensions: approx. 2,0 x 175,0 m (350 m ²) Roll width: approx. 2,0 m
Delivery form	Loose rolls
Delivery weight	approx. 80 kg per roll
Storage	Dry and UV-protected



Suggested tender text:

ClimaGrün Filter fleece CG-FV 200 prevents fines from being washed into the drainage layer and guarantees a high water permeability with the following properties:

Material PP (polypropylene), nominal thickness approx. 1,9 mm, weight approx. 200 g/m², opening width O₉₀ (EN ISO 12956) approx. 0,1 mm, static puncture resistance (EN ISO 12236) approx. 2.350 N, geotextile robustness class GRC 3, water permeability H₅₀ (EN ISO 11058) approx. 115 l/m²s, supply and lay professionally with 10 cm overlap.